

# Silhouette Paints

## Technical Data Sheet for Interior Coatings

### Metallic Colors

#### Product Description

Metallic is a water-based special effects paint that creates a variety of special metallic effects on interior walls.

#### Recommended Areas of Application

**Area of Use** : Interior  
**Substrate** : Concrete, Plaster, Masonry, Gypsum, Timber

#### Technical Data

**Sheen Variants** : Metallic  
**Colours** : Available in various shades  
**Theoretical Covering Capacity** : As per design

| Drying time | Substrate Temp. | Touch Dry   | Overcoating Interval |                |
|-------------|-----------------|-------------|----------------------|----------------|
|             |                 |             | Maximum              | Hard Dry       |
|             | 25°C            | 1 - 2 hours | 3 - 4 hours          | After 24 hours |

#### Application Data

**Method of application** : Brush, roller, sea sponge, roller with special effects, cloth, rag, etc.  
**Thinner** : Water  
**Thinning ratio (by vol.)** : If necessary

#### Surface Preparation

The performance of this coating is directly related to the degree of surface preparation.

- Ensure surface is clean, dry and free from all contaminants.
- Surface must be sound and free from laitance.
- Remove laitance by wire brush or sweep blast.

Note : Fungal growth should be treated with Silhouette Damp Proof Primer. After drying, one coat of Silhouette Damp Proof Primer should be applied.



### Special Effects

Different types of special effects such as crinkle, dapple, weaving, canvas, spatula, color wash, ragging, sponging, combing, brushing can be created using a variety of tools on Asian Paints Royale Play Metallics special effects paint.



### Easy Application

Specially formulated such that it is easy to apply, allows the tools to move smoothly, retaining the pattern left by the tool. It provides greater open time, and provides a Metallic lustre that lends elegance and style to a surface.



### Environment Friendly

It's a 100% acrylic emulsion paint for interior application. It will not run or sag on vertical surfaces. It is abrasion resistant, translucent, odourless, non-toxic, non-flammable and fully respects people's health and environment.

## Application Details

- Ensure adequate ventilation during application and drying.
- Do not apply when humidity exceeds 85% and condensation is likely.
- Surface temperature should be 3°C or more above dew point.
- Stir the contents thoroughly before and during use, with a broad flat stirrer, using an upward lifting action.

Use appropriate application tool depending on the design required to be created. It is suggested that a high quality application tool be used to ensure superior effects.

#### TYPICAL PAINT SYSTEM

1 coat x Primer/As recommended by the Company

2 coats x Basecoat Color

Royale Play Metallics as per textures

## Storage, Safety Information And Precautions

#### Storage and Handling:

- Keep out of reach of children.
- Store in cool, dry conditions; ensure adequate ventilation during application.
- Avoid contact with skin and eyes; wear suitable protective clothing such as overalls, goggles, dust masks and gloves.
- Shelf life up to 24 month is from the date of manufacture.

**First-Aid**

- Eyes : In the event of accidental splashes, flush eyes immediately with warm water and obtain medical advice.
- Skin : Wash skin thoroughly with soap and water, or with an approved industrial cleaner. Do not use solvents.
- Inhalation : Move patient to fresh air, loosen collar and keep patient rested.
- Ingestion : Do not induce vomiting. Obtain immediate medical attention.
- Dispose in landfill only.

NB: The information reported in this technical data sheet comes from our best experience; however this does not involve any responsibility of our Company for applications of this product without our control.

## Disclaimer

The information provided in this data sheet is not intended to be complete. It is the responsibility of the user to ensure that the product used is suitable for the purpose it is meant to serve. In view of various factors affecting the performance of the coating, we cannot assume responsibility for the product performance, nor do we accept any liability arising from use of this product, unless specifically agreed to in writing by us. The information provided in the data sheet may be modified by us without notice.

*This Technical Data Sheet supersedes those previously issued with immediate effect*