



SILHOUETTE PAINTS

Page 1

Page 1 of 3

TECHNICAL DATA SHEET

GLASS BULB ANTI VAPORIZING PAINT

PRODUCT DESCRIPTION

A solvent based paint, based on special resins and chemicals. The dried film gives good resistance against dry heat and protection to base substrate.

RECOMMENDED USES

As a anti vaporize topcoat paint on glass surface. At recommended thickness it has excellent heat retardant properties.

TECHNICAL DATA

COLOUR, DRY FILM	Orange (Reddish Tinge)
FINISH, DRY FILM	Smooth / Glossy
VOLUME SOLIDS (ASTM D2697)	35 ± 2%
SPECIFIC GRAVITY	0.95 ± 0.05
THEORETICAL SPREADING RANGE	8 – 10 M ₂ /LTR
RECOMMENDED DFT	10 – 15 Microns/Coat
RECOMMENDED WFT	25 – 30 Microns/Coat
DRYING TIME	Drying time @ 180°C for 30 minutes (Temperature, humidity, air movement, film thickness and number of coats all affect the drying time.)
TOUCH DRY	2 – 3 hours
DRY TO RECOAT	0 - 24 hours
HARD DRY	24 hours

ADVANTAGES ANTI VAPORIZE PAINT SYSTEM

One component special resin based paint, easy to apply, excellent water, weather and U.V. resistance. Dry film has excellent heat retardant properties.

PROTECTIVE COATINGS TECHNICAL DATA SHEET**APPLICATION INSTRUCTION****SURFACE PREPARATION**

Surface should be free of oil, grease, dust and loose particles. A sound prepared surface will lead to a better paint application. When used over old coating systems, the surface must be clean, dry and properly anchored.

For optimum service life, the surface should be completely free of con-taminants that might impair performance and should be treated to ensure good and permanent adhesion of the paint system. For removing dust and loose particles, cleaning by air cleaning is recommended.

APPLICATION DATA**APPLICATION METHOD**

Brush, Roller or Spray

CLEANING/THINNING

Thinner not required

THINNER (VOLUME)

Ready to use.

CONV. SPRAY REQUIREMENTS

Pressure: 50 psi

AIRLESS SPRAY REQUIREMENTS

Pressure : 2200 psi

NOZZLE SIZE

0.018" – 0.020"

MIXING RATIO (BY VOLUME)

Not applicable

POT LIFE @ 30°C (100 ml)

Not applicable

SYSTEM

RECOMMENDED SYSTEM To be applied on prepared surface. System as specified heat resistance up to 300°C.

TECHNICAL DATA SHEET**HEALTH & SAFETY SAFETY PRECAUTIONS**

As a general rule, avoid skin and eye contact by wearing overalls, gloves, goggles, and airmask etc. Spillage on skin should immediately be removed by thorough washing with water and soap or suitable cleaner. Eye should be flushed with fresh water. Avoid inhalation of vapours and paint mist by wearing suitable airmask. In the event of ingestion and eye contact, seek medical attention immediately. Painting must be carried out in well-ventilated area.

This as industrial product contains flammable materials and should be kept away from the sparks and open flames, smoking in the area should not be permitted. Local safety regulations should be followed.

STORAGE & HANDLING**STORAGE**

Store the paint in proper storage conditions as per the local regulations. Keep the paint container in sealed condition under shed, away from direct sunlight and extreme temperatures. Do not stock paint material near to any ignition sources. Do not put back the half or unused material back in original container, containing the supplied paint, to avoid contamination. Handle with care. Stir well before use.

ADDITIONAL DATA**SHELF LIFE @ 30°C**

18 months, in original sealed container, with proper storage conditions.

NOTE: We warranty only the quality of our product and this data sheet is based on results obtained from experience and tests. We reserve the right to change data without prior notice. For surface preparation, safety details refer specifier and safety data.

**SILHOUETTE PAINTS**

Sector – 9, Gurgaon, Haryana (India)

Phones : 9527194156

Email: silhouettpaints@icloud.com